

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1-12. (canceled)

13. (currently amended) A frequency multiband antenna comprising:

- a ~~PBG material (Photonic Bandgap)~~ Photonic Bandgap (PBG) material suitable for the spatial and frequency-wise filtering of electromagnetic waves, ~~this~~ said PBG material exhibiting at least one stopband and forming an exterior surface radiating in emission and/or in reception,

- at least one defect of periodicity of the PBG material in such a way as to create at least one narrow passband within said at least one stopband of ~~this~~ said PBG material, and

- an excitation device suitable for emitting and/or receiving electromagnetic waves inside said at least one narrow passband created by said at least one defect,

wherein:

- the excitation device is suitable for working simultaneously at least around a first and a second distinct working frequency;

- the first and the second working frequencies are situated inside respectively a first and a second narrow passband, mutually distinct, and

- the first and the second narrow passbands are created by the same defect of periodicity of the PBG material.

14. (currently amended) The antenna as claimed in claim 13, wherein the ~~periodicity~~ defect of periodicity of the PBG material creating the first and the second narrow passbands forms a leaky resonant cavity exhibiting a constant height in a direction orthogonal to said exterior ~~radiating~~ surface, and in that ~~this~~ said height is adapted so as to place the first and the second narrow passbands within said at least one stopband of the PBG material.

15. (previously presented) The antenna as claimed in claim 14, wherein the height of the cavity is adapted so as to place the first and the second narrow passbands within one and the same stopband of the PBG material.

16. (previously presented) The antenna as claimed in claim 14, wherein the PBG material exhibits a first and a second mutually spaced disjoint stopband, and the height of the cavity is adapted so as to place the first and the second narrow

passbands within respectively the first and the second stopbands of the PBG material.

17. (previously presented) The antenna as claimed in claim 13, wherein said first narrow passband is substantially centered on a fundamental frequency, while said second narrow passband is substantially centered on an integer multiple of this fundamental frequency.

18. (currently amended) The antenna as claimed in claim [[13]] 14, wherein the cavity exhibits a family of resonant frequencies formed by a fundamental frequency and its harmonics, the resonant mode of the cavity and the radiation pattern of the antenna being the same for each resonant frequency of the family, and the first and the second working frequencies each correspond, in their respective narrow passband, to a frequency of the same family.

19. (currently amended) The antenna as claimed in claim [[13]] 14, wherein the cavity exhibits at least two families of resonant frequencies each formed by a fundamental frequency and its harmonics, ~~the~~ a resonant mode and ~~the~~ a radiation pattern of the antenna being the same for each resonant frequency of one and the same family and different from those of the other families of resonant frequencies, and the first and the

second working frequencies each correspond, in their respective narrow passband, to frequencies belonging to different families.

20. (previously presented) The antenna as claimed in claim 13, wherein the excitation device is able to emit electromagnetic waves at the first working frequency having a different polarization from the electromagnetic waves emitted at the second working frequency.

21. (previously presented) The antenna as claimed in claim 13, wherein the excitation device comprises at least one same excitation element suitable for emitting and/or for receiving electromagnetic waves simultaneously at the first and at the second working frequencies.

22. (previously presented) The antenna as claimed in claim 13, wherein the excitation device comprises a first and a second excitation element each suitable for emitting and/or for receiving electromagnetic waves, and the first excitation element is suitable for working at the first working frequency, while the second excitation element is suitable for working at the second working frequency.

23. (previously presented) The antenna as claimed in claim 22, wherein each of the excitation elements is able to

generate, on said exterior surface, respectively a first and a second mutually disjoint radiating spot, each of these radiating spots representing the origin of an electromagnetic wave beam radiated in emission and/or in reception by the antenna.

24. (currently amended) The antenna as claimed in claim [[13]] 14, wherein the leaky resonant cavity is of parallelepipedal shape.